

## **SAFETY DATA SHEET**

## Section 1. Identification of the material and the supplier

Product: Degafiller 332

Product Use: Main applications (non-exhaustive list): Filler for industrial

floor coatings

Restriction of Use in NZ: Refer to Section 15

Company Name: **Degafloor NZ**Address: 6 Sheffield Street
Levin, 5510

Telephone: +64 6 367 9799
E-mail: orders@degafloor.nz

Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 15 September 2020

## Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: Surface Coatings and Colourants (subsidiary) - HSR002670

## **Pictograms**



Chronic

Signal Word: DANGER

This product contains fine fraction quartz. Specific target organ toxicity repeated exposure respiratory tract irritation STOT RE 1.

Depending on the type of handling and use (e.g. grinding), airborne fine fraction crystalline silica may be generated. Prolonged and/or massive inhalation of fine fraction crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness. Occupational exposure to fine fraction crystalline silica dust should be monitored and controlled.

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
6.9A	H372	Causes damage to lungs through prolonged or repeated exposure via inhalation	STOT RE 1

<b>Prevention Code</b>	Prevention Statement
P103	Read label before use.
P260	Do not breathe dust.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.

Product Name: Degafiller 332 SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 15 September 2020 Tel: 64 9 475 5240 www.techcomp.co.nz

Response Code	Response Statement
P314	Get medical advice/attention if you feel unwell.

Storage Code	Storage Statement	
None allocated	Store locked up.	

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

## Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Quartz sand	0 - 90	14808-60-7
Quartz flour	10 - 90	14808-60-7
Barium sulphate	0 - 70	7727-43-7
Treated glass beads	0 - 20	65997-17-3

## Section 4. First Aid Measures

## Routes of Exposure:

If in Eyes Don't chafe for avoiding damage of cornea. If necessary, remove contact

lenses. Rinse with copious quantities of water. If available, use isotonic flushing solution (0.9 wt.-% Sodium chloride). If irritation persists, seek

medical attention

If on Skin Wash skin thoroughly with soap and water. Get medical advice/attention.

If Swallowed Never give anything by mouth to an unconscious person.

Clean mouth with water and drink afterwards plenty of water. Seek

medical attention if needed.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes

difficult.

## Most important symptoms and effects, both acute and delayed

Symptoms: Prolonged and/or massive exposure to fine fraction crystalline silica-

containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine fraction particles of crystalline silica.

## **Section 5.** Fire Fighting Measures

Hazard Type	Non Flammable or non-combustible.
Hazards from	No hazardous thermal decomposition. Thermal decomposition of barium
products	sulphate (1580°C) produces sulfur dioxide.
Suitable	No specific extinguishing media is needed.
Extinguishing	
media	
Precautions for	No special measures required.
firefighters and	
special protective	
clothing	
HAZCHEM CODE	None allocated

Product Name: Degafiller 332 SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 15 September 2020 Tel: 64 9 475 5240 www.techcomp.co.nz

## Section 6. Accidental Release Measures

## **Personal precautions:**

Use protective clothing as detailed in Section 8. Keep out unprotected persons. Avoid airborne dust generation.

#### **Environmental precautions:**

No special precautions.

## Spill and Disposal procedures:

Avoid dry sweeping and use water spraying or vacuum cleaning systems to prevent airborne dust generation. Dispose according to Section 13.

## Section 7. Handling and Storage

### **Precautions for Handling:**

- Read label before use.
- Do not breathe dust.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Avoid airborne dust generation.
- Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment, e.g. EN 149.
- Handle packaged product carefully to prevent accidental bursting.

## **Precautions for Storage:**

- Store away from incompatible materials listed in Section 10.
- Minimize airborne dust generation and prevent wind dispersal during loading and unloading.
- Keep containers closed and store packaged products so as to prevent accidental bursting.

## Section 8 Exposure Controls / Personal Protection

#### WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA ppm	mg/m³	STEL ppm	mg/m³
Respirable crystalline silica dust:	8 hours	1	0.1	-	-
Barium sulphate	[7727-43-7]	-	10	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2019  $11^{TH}$  EDITION.

## **Engineering Controls**

Minimize airborne dust generation. Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne particles below the exposure limit. Apply organizational measures, e.g. by isolating personal from dusty areas. Remove and wash soiled clothing.

## **Personal Protection Equipment**

Product Name: Degafiller 332 SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 15 September 2020 Tel: 64 9 475 5240 www.techcomp.co.nz



Eyes	Wear safety glasses with side-shields in circumstances where there is a risk of penetrative eye injuries according to EN 166.
Hands	Appropriate protection [e.g. gloves according to EN 374 or nitrile impregnated cotton gloves according to specification EN 374, barrier cream] is recommended for workers who suffer from dermatitis or sensitive skin. Wash hands at the end of each work session.
Skin	No specific requirement. For hands, see below. Appropriate protection (e.g. protective clothing, barrier cream) is recommended for workers who suffer from dermatitis or sensitive skin.
Respiratory	In case of prolonged exposure to airborne dust concentrations, wear respiratory protective equipment that complies with the requirements of European or national legislation.

#### Section 9 **Physical and Chemical Properties**

Appearance	Solid (granular/powder)
Colour	Grey
Odour	Odourless
Odour Threshold	Not available
pH	Approx 6-8
Boiling Point	Not available
Freezing/Melting Point	Not relevant, >1300°C
Flash Point	Not available
Flammability	Not available
Upper and Lower	Not available
<b>Explosive Limits</b>	
Vapour Pressure	Not available
Vapour Density (air=1)	Not available
Specific Gravity	Approx. 2,6 – 3,6g/mL
Water Solubility	Solubility in water: negligible
	Solubility in hydrofluoric acid: yes
Partition Coefficient:	Not available
Auto-ignition	Not applicable (not pyrophoric - no organo-metallic, organo-
Temperature	semimetal or organo-phosphane bonds or derivatives and no
	other pyrophoric components).
Minimum ignition	Not available
temperature:	
Decomposition	Not available
Temperature	
Dynamic Viscosity	Not available

# Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous	Is inert and not reactive
reactions	
Conditions to Avoid	No conditions to avoid.
Incompatible Materials	None known.
<b>Hazardous Decomposition</b>	No hazardous decomposition products in regular use
Products	

#### **Section 11 Toxicological Information**

# **Acute Effects:**

Product Name: Degafiller 332 Date of SDS: 15 September 2020 SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Tel: 64 9 475 5240 www.techcomp.co.nz

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Not applicable.

#### **Chronic Effects:**

Carcinogenicity	Not applicable.
Reproductive	Not applicable.
Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Causes damage to lungs through prolonged or repeated exposure via
	inhalation.

## Section 12. Ecotoxicological Information

Quartz is a natural mineral and widely spread on earth and is nontoxic to aquatic organism and could be separated from waste water by settlement.

Persistence and degradability	No data available.	
Bioaccumulation	No data available.	
Mobility in Soil	Negligible	
Other adverse effects	No specific injurious effects are known. However, this	
	doesn't exclude the possibility that large or frequent spills	
	can have a harmful or damaging effect on the environment.	

## Section 13. Disposal Considerations

## **Disposal Method:**

Where possible, recycling is preferable to disposal. Can be disposed of in compliance with local regulations.

## **Contaminated Packaging:**

Dust formation from residues in packaging should be avoided and suitable worker protection assured. Store used packaging in closed receptacles. Recycling and disposal of packaging should be carried out in compliance with local regulations.

Precautions or methods to avoid: None known.

#### **Section 14 Transport Information**

## This product is NOT classified as a Dangerous Good for transport in NZ; NZS 5433:2012

#### Section 15 **Regulatory Information**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (subsidiary) - HSR002670

HSNO Classification: 6.9A

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	Not required
Tracking Trigger Quantities	Not required

Product Name: Degafiller 332 SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 15 September 2020 Tel: 64 9 475 5240 www.techcomp.co.nz

Signage Trigger Quantities	Not required
Emergency Response Plan	10 000 kg(6.9A)
Secondary Containment	10 000 kg (6.9A)
Restriction of Use	Only use for the intended purpose.

#### **Section 16** Other Information

Glossary

 $EC_{50}$ Median effective concentration. FFI Environmental Exposure Limit. **EPA Environmental Protection Authority** 

**HSNO** Hazardous Substances and New Organisms.

**HSW** Health and Safety at Work.

Lethal concentration that will kill 50% of the test organisms  $LC_{50}$ 

inhaling or ingesting it.

LD<sub>50</sub> Lethal dose to kill 50% of test animals/organisms.

Lower explosive level. LEL

**OSHA** American Occupational Safety and Health Administration.

Tolerable Exposure Limit. TFI

TLV Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level WES Workplace Exposure Limit

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017

2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.

3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).

4. Transport of Dangerous goods on land NZS 5433:2012

5. HSW (Hazardous Substances) Regulations 2017

#### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-todate information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact Degafloor NZ, if further information is required.

Issue Date: 15 September 2020 Review Date: 15 September 2025

Product Name: Degafiller 332 SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 15 September 2020 Tel: 64 9 475 5240 www.techcomp.co.nz