

**DEGADUR® 420**

Middle-viscous elasticized methacrylate resin for manufacturing of 2-component floor coatings. For trowel application, self-levelling, smooth or broadcast indoor coatings on concrete and metal surfaces. For wet and dry areas.

**Typical properties**

Property	Value	Unit	Method
Form supplied	Slightly turbid liquid		
Viscosity at 23 °C	160 - 200	mPas	Brookfield DV2, sp. 2/60 rpm
Density at 20 °C	1.01	g/cm <sup>3</sup>	DIN 51757
T <sub>max</sub> at 23 °C	18 - 26 min / 140 - 165 °C		70.0 g DEGADUR® 420 + 1.4 g BPO 50%
Flash point	10	°C	MMA, DIN 51755

**General remarks**

Activator	DEGADUR® 420 is preactivated for temperatures from 5 °C to 30 °C
Initiator/Hardener	BPO-Hardener (50 %), depending on temperature
Shelf life	at ≤ 25 °C minimum 12 months in original containers / from date of delivery at ≤ 30 °C minimum 6 months in original containers / from date of delivery
Storage	Protect against direct sunlight. At temperatures below 15 °C the paraffin dissolved in the binder may precipitate. The material must be stirred thoroughly before use.
Packaging	Steel drum, 190 kg net

**DEGADUR® 420****Properties**

DEGADUR® 420 coatings can be highly filled and have good levelling properties. DEGADUR® 420 is preferably used as a self levelling coating in coat thicknesses of 2 - 4 mm because of its good wetting power of fillers and pigments. Broadcast, paint-roller and trowel applied systems are also possible.

**Guide formulations:****420/1 - self-leveling / smooth / pigmented or broadcast with flakes / 2 - 4 mm**

30	% by wt.	DEGADUR® 420
20.5	% by wt.	fine filler 0 - 50 µm (no filler based on carbonate!)
47.5	% by wt.	quartz sand (0.06 - 0.3 mm)
2	% by wt.	pigment powder

**Guide formulations:****420/2 - self-leveling coating / broadcast with coloured sand / 3 - 5 mm**

26	% by wt.	DEGADUR® 420
22	% by wt.	fine filler 0 - 50 µm (no filler based on carbonate!)
51	% by wt.	quartz sand (0.06 - 0.3 mm)
1	% by wt.	pigment powder

**Guide formulations:****420/3 - trowel applied coating / 4 - 6 mm**

22.5	% by wt.	DEGADUR® 420
59.5	% by wt.	coloured quartz sand or quartz sand (0.7 - 1.2 mm)
18	% by wt.	coloured quartz sand or quartz sand (0.1 - 0.4 mm)

**Guide formulations:****420/4 - vertical application / 0.5 - 2 mm**

79	% by wt.	DEGADUR® 420
10	% by wt.	pigment powder
10	% by wt.	fine filler 0 - 50 µm (no filler based on carbonate!)
1	% by wt.	Sylothix 51

## DEGADUR® 420

### Application

The DEGADUR® **420/1** and **420/2** formulations are applied with a trowel or an adjustable-rake in a minimum thickness of 2 mm. For smooth surfaces a refinishing with a spiked roller is advisable.  
For decorative surfaces, coloured flakes (3 - 4 mm), coloured quartz sand (coated with EP or PU resin) or Granodiorite with a size of 0.3 - 0.8 mm or 0.7 - 1.2 mm can be broadcast onto the self-levelling formulation.

The application of the DEGADUR® **420/3** mixture takes place with an adjustable-rake and is afterwards smoothed with a flexible trowel.

The total catalysed quantity of **420/4** formulation is completely poured out onto the primed substrate, distributed by means of a finely serrated (2 - 4 mm teeth) rubber blade and rolled out with a nylon-roller (12 - 14 mm pile woven).

The surface of DEGADUR® 420 coatings need a clear or pigmented DEGADUR® topcoat.

### Pot life and hardening time at different temperatures::

Formulations 420/1, 420/2, 420/3, 420/4

Temperature [°C] **)	Hardener [% by wt.] *)	Pot life [min] ***)	Hardening time [min]
5	4.0	approx. 35	approx. 65
10	2.5	approx. 30	approx. 65
15	2.0	approx. 30	approx. 55
20	1.0	approx. 25	approx. 45
25	1.0	approx. 15	approx. 30
30	1.0	approx. 13	approx. 30

\*) Quantity calculated on DEGADUR® 420.

\*\*) Temperature statements refer to resin-, floor- and air-temperature.

\*\*\*) The indication of the approximate pot life always refers to the lower temperature.

Note: All values are derived from laboratory tests. Deviations caused by environmental factors might occur.

### More accounts

All formulations have to be applied on preprimed surfaces!

Before top coat is applied onto a body coat which had been scattered with flakes, it is essential to grind the surface by means of a dedicated grinding facility, e.g. soft nylpads. Subsequently all the not fixed particles must be removed. This step avoids unevenness and micro bubbles.

Use efficient air ventilation in order to provide a safe surface curing.

**DEGADUR® 420**

Typical properties are approximate reference values. If you need product specifications please contact us.

® = registered trademark of Röhm or affiliates

DEGADUR is a registered trademark of Röhm GmbH, Darmstadt, Germany.

---

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

**Röhm GmbH**  
Deutsche-Telekom-Allee 9  
64295 Darmstadt  
Germany  
PHONE +49 6241 402-0

**Roehm America LLC**  
299 Jefferson Road  
Parsippany,  
NJ 07054 USA  
PHONE +1 973 929-8000

**Roehm Chemical (Shanghai) Co., Ltd.**  
55 Chundong Road,  
Xinzhuang Industry Park  
Shanghai 201108, China  
PHONE +86 21 6119 1616

Product Information  
14.04.2021  
DEGADUR 420 e  
Page 4/4