

## DEGAROUTE® 465

Methacrylate resin for durable cold plastic road markings

### Description

- low viscosity methacrylate resin used as a binder for permanent markings based on cold plastic
  - permanently elastic and is processed without plasticizers
  - viscosity of ready formulated material is stable over a long period
  - versatile use as: flat line, profiled and structure markings
  - recommended surface temperature for application is between 5 °C and 60 °C
  - tested by BaSt (Federal Road Research Institute of Germany)
  - good wetting properties for fillers and pigments, outstandingly fluid cold plastics can be produced
  - for use in cold and warm climates
- 
- applications at temperatures below 5 °C are possible by addition of Accelerator 50 (see data sheet "Application of Cold Plastic and Cold Spray Plastic below 5 °C (+41°F)")

### Applications

- markings at junctions and crossings, stop lines and direction arrows
- centre markings on freeways and highways
- manual application by trowel and draw box

### Equipment

- manual application by trowel and draw box
- application by hand guided machines
- application by 2-component extrusion machines with 100:2 dosing
- application by draw box (100:2 system), even for profiled and structure markings
- application by 2-component machines with 1:1 dosing (see DEGAROUTE® 469)

### Properties

- suitable for high temperatures
- permanently elastic
- resistant to ageing and weathering
- colorfast
- abrasion-proof
- resistant to de-icing salt and fuels
- low tendency to graying

## DEGAROUTE® 465

Methacrylate resin for durable cold plastic road markings

### Product properties

Property	Value	Unit	Method
Form supplied	liquid		
Flow time at 23 °C	75 - 95	s	ISO 2431, 4 mm cup
Viscosity at 23 °C	approx. 170	mPas	Brookfield DV2, sp. 2/12 rpm
Density at 20 °C	0.97	g/cm <sup>3</sup>	DIN 51757
Refractive index $n_D^{20}$	1.44		DIN 51423
Color value	< 50		APHA
Flash point	11	°C	DIN 51755

### General remarks

Shelf life	at ≤ 25 °C minimum 12 months in original containers / from date of delivery at ≤ 30 °C minimum 6 months in original containers / from date of delivery
	This product contains max. 10 g/l residual volatiles (ASTM 2369 Method E).

### Typical formulations:

465 - 1 / 1 - 3 mm / 100:2 system / flat: for hand, draw box or machine application

		pbw
Binder / resin	DEGAROUTE® 465	20.00
Dispersing additive	Disperbyk 167	0.10
Rheology additive	Byk D 410	0.10
Rheology additive	Bentone 27	0.10
Pigment (TiO <sub>2</sub> )	Tioxide TR 92	10.00
Fine filler (15 µm)	Omyacarb 15GU	20.00
Coarse filler (0.1 - 0.4 mm)	Cristobalite M72	25.00
Premix beads	50 - 250 µm	25.00

### Properties

Viscosity at 23 °C:	between 8 - 9 cm	blot test for CP
Viscosity at 23 °C:	between 13 - 14	Daniel flow gauge
Shore D hardness:	50 - 60	DIN 53505
Density:	1.85 g/cm <sup>3</sup>	DIN 51757
Consumption:	approx 3.7 kg/m <sup>2</sup>	for 2 mm thickness

## DEGAROUTE® 465

Methacrylate resin for durable cold plastic road markings

### Typical formulations:

465 - 2 / up to 7 mm / 100:2 system / profile: application with suitable machines with profile function

		pbw
Binder / resin	DEGAROUTE® 465	20.00
Dispersing additive	Disperbyk 167	0.10
Rheology additive	Byk D 410	0.15
Rheology additive	Bentone 27	0.15
Pigment (TiO <sub>2</sub> )	Tioxide TR 92	10.00
Fine filler (15 µm)	Omyacarb 15GU	20.00
Coarse filler (0.1 - 0.4 mm)	Cristobalite M72	25.00
Premix beads	50 - 250 µm	25.00

### Properties

Viscosity at 23 °C:	approx. 6 cm	blot test for CP
Viscosity at 23 °C:	between 10 - 12	Daniel flow gauge
Shore D hardness:	50 - 60	DIN 53505
Density:	1.85 g/cm <sup>3</sup>	DIN 51757
Consumption:	4 - 6 kg/m <sup>2</sup>	depending on used profile

### Typical formulations:

465 - 3 / up to 7 mm / 100:2 structure: application with suitable structure machines

		pbw
Binder / resin	DEGAROUTE® 465	20.00
Dispersing additive	Disperbyk 167	0.10
Rheology additive	Byk D 410	0.20
Rheology additive	Bentone 27	0.20
Pigment (TiO <sub>2</sub> )	Tioxide TR 92	10.00
Fine filler (15 µm)	Omyacarb 15GU	25.00
Coarse filler (0.1 - 0.4 mm)	Cristobalite M72	20.00
Premix beads	100 - 600 µm	25.00

### Properties

Viscosity at 23 °C:	approx. 6 cm	blot test for CP
Viscosity at 23 °C:	between 10 - 12	Daniel flow gauge
Shore D hardness:	42 - 52	DIN 53505
Density:	1.85 g/cm <sup>3</sup>	DIN 51757
Consumption:	approx 1.5 - 3 kg/m <sup>2</sup>	depending on used structure

## DEGAROUTE® 465

Methacrylate resin for durable cold plastic road markings

### Typical formulations:

465 - 4 / up to 7 mm / 100:2 structure: application with suitable structure machines

		pbw
Binder / resin	DEGAROUTE® 465	20.00
Dispersing additive	Disperbyk 167	0.15
Rheology additive	Byk D 410	0.10
Rheology additive	Bentone 27	0.20
Pigment (TiO <sub>2</sub> )	Tioxide TR 92	10.00
Fine filler (5 µm)	Omyacarb 5GU	15.00
Coarse filler (0.5 - 1.0 mm)	Minigrain 1	30.00
Premix beads	100 - 600 µm	25.00

### Properties

Viscosity at 23 °C:	6 - 7 cm	blot test for CP
Viscosity at 23 °C:	between 10 - 12	Daniel flow gauge
Shore D hardness:	not determined	DIN 53505
Density:	1,92 g/cm <sup>3</sup>	DIN 51757
Consumption:	1.5 - 3 kg/m <sup>2</sup>	depending on used structure

### Pot life and setting time

Typical formulations 465 - 1, 465 - 2, 465 - 3 and 465 - 4

Approved hardener: hardener powder, as a proportion of total formulation

Temperature (°C) (surface)	Hardener (50 % DBPO) (% by weight)	Pot life (min)	Setting time (min)
10	3.0	14	45
10	2.0	18	50
20	2.0	10	30
20	1.0	15	35
30	1.0	8	20
30	0.5	12	30
40	0.5	6	18

Note: All values are derived from laboratory test. Deviations caused by environmental factors might occur.

## DEGAROUTE® 465

Methacrylate resin for durable cold plastic road markings

### Note

Manual dosage of hardener powder can use mixing ratios from the table.

Automatic dosage of hardener usually uses a mixing ratio between 1.5 - 2 %.

### Performance test

Flat marking: BaSt certificate 20011DK0407

Structure marking: BaSt certificate 20011DK0314

Typical properties are approximate reference values. If you need product specifications please contact us.

® = registered trademark of Röhm or affiliates

DEGAROUTE is a registered trademark of Röhm GmbH, Darmstadt, Germany.

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

**Röhm GmbH**  
Dolivostraße 17  
64293 Darmstadt  
Germany  
PHONE +49 6241 402-0

**Roehm America LLC**  
299 Jefferson Road  
Parsippany,  
NJ 07054 USA  
PHONE +1 973 929-8000

**Roehm Chemical (Shanghai) Co., Ltd.**  
55 Chundong Road,  
Xinzhuang Industry Park  
Shanghai 201108, China  
PHONE +86 21 61191 1616

Product Information  
18.05.2018  
DEGAROUTE 465 e  
Page 5/5